Logiciel

Fichier /etc/nginx/sites-available/default

/etc/nginx/sites-available/default

```
##
# You should look at the following URL's in order to grasp a solid
understanding
# of Nginx configuration files in order to fully unleash the power
of Nginx.
# https://www.nginx.com/resources/wiki/start/
#
https://www.nginx.com/resources/wiki/start/topics/tutorials/config
_pitfalls/
# https://wiki.debian.org/Nginx/DirectoryStructure
#
# In most cases, administrators will remove this file from sites-
enabled/ and
# leave it as reference inside of sites-available where it will
continue to be
# updated by the nginx packaging team.
#
# This file will automatically load configuration files provided
by other
# applications, such as Drupal or Wordpress. These applications
will be made
# available underneath a path with that package name, such as
/drupal8.
#
# Please see /usr/share/doc/nginx-doc/examples/ for more detailed
examples.
##

# Default server configuration
#
server {
    listen 80 default_server;
    listen [::]:80 default_server;

    # SSL configuration
    #
    # listen 443 ssl default_server;
    # listen [::]:443 ssl default_server;
    #
    # Note: You should disable gzip for SSL traffic.
    # See: https://bugs.debian.org/773332
    #
    # Read up on ssl_ciphers to ensure a secure configuration.
```

```
    # See: https://bugs.debian.org/765782
    #
    # Self signed certs generated by the ssl-cert package
    # Don't use them in a production server!
    #
    # include snippets/snakeoil.conf;

    root /var/www/html;

    # Add index.php to the list if you are using PHP
    index index.html index.htm index.nginx-debian.html;

    server_name _;

    location / {
        # First attempt to serve request as file, then
        # as directory, then fall back to displaying a 404.
        try_files $uri $uri/ =404;
    }

    # pass PHP scripts to FastCGI server
    #
    #location ~ \.php$ {
    #    include snippets/fastcgi-php.conf;
    #
    #    # With php-fpm (or other unix sockets):
    #    fastcgi_pass unix:/run/php/php7.3-fpm.sock;
    #    # With php-cgi (or other tcp sockets):
    #    fastcgi_pass 127.0.0.1:9000;
    #}

    # deny access to .htaccess files, if Apache's document root
    # concurs with nginx's one
    #
    #location ~ /\.ht {
    #    deny all;
    #}
}


# Virtual Host configuration for example.com
#
# You can move that to a different file under sites-available/ and
symlink that
# to sites-enabled/ to enable it.
#
#server {
#   listen 80;
#   listen [::]:80;
```

```
#
#   server_name example.com;
#
#   root /var/www/example.com;
#   index index.html;
#
#   location / {
#       try_files $uri $uri/ =404;
#   }
#}
```

Voir aussi

- **(fr)** Article
- **(en)** Article

Basé sur « Article » par Auteur.

From:
http://doc.wikis.frapp.fr/ - **doc**

Permanent link:
http://doc.wikis.frapp.fr/doku.php?id=logiciel:reseau:http:serveur:nginx:raspi:default:start

Last update: **2024/09/21 10:43**