

Logiciel

Fichier /etc/nginx/sites-available/default

/etc/nginx/sites-available/default

```
##  
# You should look at the following URL's in order to grasp a solid  
understanding  
# of Nginx configuration files in order to fully unleash the power  
of Nginx.  
# https://www.nginx.com/resources/wiki/start/  
#  
https://www.nginx.com/resources/wiki/start/topics/tutorials/config_ _pitfalls/  
# https://wiki.debian.org/Nginx/DirectoryStructure  
#  
# In most cases, administrators will remove this file from sites-  
enabled/ and  
# leave it as reference inside of sites-available where it will  
continue to be  
# updated by the nginx packaging team.  
#  
# This file will automatically load configuration files provided  
by other  
# applications, such as Drupal or Wordpress. These applications  
will be made  
# available underneath a path with that package name, such as  
/drupal8.  
#  
# Please see /usr/share/doc/nginx-doc/examples/ for more detailed  
examples.  
##  
  
# Default server configuration  
#  
server {  
    listen 80 default_server;  
    listen [::]:80 default_server;  
  
    # SSL configuration  
    #  
    # listen 443 ssl default_server;  
    # listen [::]:443 ssl default_server;  
    #  
    # Note: You should disable gzip for SSL traffic.  
    # See: https://bugs.debian.org/773332  
    #  
    # Read up on ssl_ciphers to ensure a secure configuration.
```

```
# See: https://bugs.debian.org/765782
#
# Self signed certs generated by the ssl-cert package
# Don't use them in a production server!
#
# include snippets/snakeoil.conf;

root /var/www/html;

# Add index.php to the list if you are using PHP
index index.html index.htm index.nginx-debian.html;

server_name _;

location / {
    # First attempt to serve request as file, then
    # as directory, then fall back to displaying a 404.
    try_files $uri $uri/ =404;
}

# pass PHP scripts to FastCGI server
#
#location ~ \.php$ {
#    include snippets/fastcgi-php.conf;
#
#    # With php-fpm (or other unix sockets):
#    fastcgi_pass unix:/run/php/php7.3-fpm.sock;
#    # With php-cgi (or other tcp sockets):
#    fastcgi_pass 127.0.0.1:9000;
#}

# deny access to .htaccess files, if Apache's document root
# concurs with nginx's one
#
#location ~ /\.ht {
#    deny all;
#}
}

# Virtual Host configuration for example.com
#
# You can move that to a different file under sites-available/ and
# symlink that
# to sites-enabled/ to enable it.
#
#server {
#    listen 80;
#    listen [::]:80;
```

```
#  
#      server_name example.com;  
#  
#      root /var/www/example.com;  
#      index index.html;  
#  
#      location / {  
#          try_files $uri $uri/ =404;  
#      }  
#}
```

Voir aussi

- [\(fr\) Article](#)
- [\(en\) Article](#)

Basé sur « [Article](#) » par Auteur.

From:
<https://doc.wikis.frapp.fr/> - doc

Permanent link:
<https://doc.wikis.frapp.fr/doku.php?id=logiciel:reseau:http:serveur:nginx:raspi:default:start> 

Last update: **2024/09/21 10:43**